



**WELLS
CARGO®**

MOTORTRAC® RACE TRAILERS

OUR FLAGSHIP MOTORSPORTS TRAILER

PERFORMANCE THAT'S TRUE TO FORM!

The MotorTrac® Race Trailer from Wells Cargo® is all about delivering performance.

Performance on the road . . .

Performance at the track . . .

Performance year after year.

Successful racers are constantly searching for superior performance, it makes sense to use top-notch equipment like the flagship MotorTrac® Racing Trailer.



Trailers shown may feature optional equipment available at an additional charge.



SPECIFICATIONS



	MT8520T3	MT8524T3	MT8528T4	MT8532R4
Body:				
Length	20' 0"	24' 0"	28' 0"	32' 0"
Width	8' 4"	8' 4"	8' 4"	8' 4"
Overall:				
Length	24' 7"	28' 7"	32' 7"	36' 7"
Width	8' 6"	8' 6"	8' 6"	8' 6"
Height (to top of roof vent)	9' 1"	9' 1"	9' 3"	9' 3"
Interior:				
Length	19' 8"	23' 8"	27' 8"	31' 8"
Width	8' 1"	8' 1"	8' 1"	8' 1"
Height	6' 10"	6' 10"	6' 10"	6' 10"
Width Between Wheel Boxes	83"	83"	83"	83"
Height of Wheel Box from Floor	10"	10"	10"	10"
Platform Height at Beavertail	19"	19"	21"	21"
Torflex® Suspension E-Z Lube® Axles: Qty	Tandem	Tandem	Tandem	Triple
Brakes with Breakaway Kit	Electric Drum	Electric Drum	Electric Drum	Electric Drum
Radial Tire Size	ST225/75R15	ST225/75R15	ST235/80R16	ST235/80R16
Tire Load Range	E	E	E	E
Hitch Ball Size	2-5/16"	2-5/16"	2-5/16"	2-5/16"
Hitch Height to Top of Ball	20"	20"	22"	22"
Hitch Weight (% of Curb Weight)	10% to 15%	10% to 15%	10% to 15%	10% to 15%
GVWR	9,900 lbs.	9,900 lbs.	12,000 lbs.	18,000 lbs.
Rear Ramp Door Opening - Width x Height	94" x 78"	94" x 78"	94" x 78"	94" x 78"
12v Male Connection	7-way	7-way	7-way	7-way
Tube Main Rails	2" x 6"	2" x 6"	2" x 8"	2" x 8"
Beavertail	32"	48"	72"	72"

STANDARD FEATURES

- Flat Front/Flat Roof Design
- Roof and Sidewall Structure
 - 16" OC Floor Crossmembers
 - 16" OC Tube Wall Posts
 - 16" OC Tube Roof Structure
- 54" A-Frame with Center Tube
- .030 Aluminum Exterior, Smooth Bonded
- Cast Aluminum Corners (Front & Rear)
- Stainless Steel Cap and Front Corners
- Chrome Rear Corners and Header
- 1-Piece Aluminum Roof
- ArmorTech® on A-Frame and Rear End Rail
- 24" ATP Stoneguard
- Spring-Assisted Rear Ramp Door with 94"W Opening
- Paddle Latch Style Handles on Rear Ramp Door
- 36" x 78" Side Entry Door with Recessed Step
- Spread Torflex® Axle Design with Drop Skirting
- Goodyear® Radial Tires* with Black SpitFire™ Aluminum Wheels
- 12v Clear Lens LED Exterior Clearance Lights
- Clear Lens Slim Line Tail Light (2 Pair)
- 12v LED Dome Lights with Wall Switch (4)
- 14" x 14" Non-Powered Roof Vent (2)
- 5,000 lbs. Square D-Rings with Welded Plate (4)
- 3/4" PlexCore™ Decking
- 3/8" PlexCore™ Sidewall Liner
- 16" PlexCore™ Ramp Extension
- 3-Year Limited Warranty



Turbo package with additional optional equipment available at additional cost.

*Trailers equipped with 7,000 lb. axles do not have Goodyear® tires as standard equipment.



www.wellscargo.com

Specifications, features, options, packages & pricing subject to change **without notice**. See your authorized Wells Cargo® dealer for more information.