



**WELLS
CARGO®**

THE ALL NEW ALUMINUM SPORTTRAC™

GO PLACES FEW HAVE BEEN

The new Wells Cargo® aluminum SportTrac mid-deck is your no limits trailer for all your powersport toys. Ramp doors, front & rear, for quick takeoffs on arrival and easy loading when heading back home. The mid-deck platform height is a hybrid design with drive over wheel boxes. Perfect for all your off-road throttle machines.



Trailers shown may feature optional equipment available at an additional charge.

SPORTTRAC
SS

SPECIFICATIONS



		STM8522T2	STM8522T3	STM8528T2	STM8528T3
Body:	Length	22' 0"	22' 0"	28' 0"	28' 0"
	Width	8' 4"	8' 4"	8' 4"	8' 4"
Overall:	Length	24' 9"	24' 9"	30' 9"	30' 9"
	Width	8' 6"	8' 6"	8' 6"	8' 6"
	Height	9' 0"	9' 0"	9' 0"	9' 0"
Interior:	Length (including "V")	21' 8"	21' 8"	27' 8"	27' 8"
	Width	8' 1"	8' 1"	8' 1"	8' 1"
	Height	7' 0"	7' 0"	7' 0"	7' 0"
Width Between Wheel Boxes		78½"	78½"	78½"	78½"
Platform Height		19"	19"	19"	19"
Torflex® Suspension E-Z® Lube Axles:		Tandem	Tandem	Tandem	Tandem
Qty		7,000 lbs.	7,000 lbs.	7,000 lbs.	7,000 lbs.
Total GAWR		10° Up	10° Up	10° Up	10° Up
Type					
Electric Brakes with Breakaway Kit		Electric Drum	Electric Drum	Electric Drum	Electric Drum
Radial Tire Size		ST205/75R15	ST225/75R15	ST205/75R15	ST225/75R15
Tire Load Range		C	D	C	D
Hitch Ball Size		2-5/16"	2-5/16"	2-5/16"	2-5/16"
Hitch Height to Top of Ball		18"	18"	18"	18"
Hitch Weight (% of Curb Weight)		10% to 15%	10% to 15%	10% to 15%	10% to 15%
GVWR		7,000 lbs.	9,990 lbs.	7,000 lbs.	9,990 lbs.
Curb Weight (Approximate)		3,140 lbs.	3,190 lbs.	3,840 lbs.	3,890 lbs.
Payload Capacity (Approximate)		3,860 lbs.	6,800 lbs.	3,160 lbs.	6,100 lbs.
Flush Lock Side Door Width		36"	36"	36"	36"
Front Ramp Door Opening - Width x Height		78" x 78"	78" x 78"	78" x 78"	78" x 78"
Rear Ramp Door Opening - Width x Height		94" x 84"	94" x 84"	94" x 84"	94" x 84"
Beavertail Length		48"	48"	48"	48"
12v Male Connection		7-way	7-way	7-way	7-way

STANDARD FEATURES

- 6' V-Front with Polished Aluminum Front Nose
- Mid-Deck Platform with Drive Over Wheel Boxes
- Rear Ramp Door with 12" Premium Aluminum Ramp Extension
- Front Ramp Door with Ski Guide
- 36" Side Entry Door with Fold Down Step (*Road Side*)
- All-Aluminum Hardware
- Aluminum Tube Perimeter Frame
- Fully Integrated, All Tube, Roof and Sidewall Design
 - 16" OC Tube Floor Crossmembers
 - 16" OC Tube Wall Posts
 - 16" OC Tube Roof Framing
- 3-Piece A-Frame with 2000 lb. Front Wind Tongue Jack
- Aluminum Fenderettes
- Torflex® Torsion Axles
- Goodyear® Radial Tires with Silver SpitFire Aluminum Wheels
- 3/4" PlexCore™ High-Performance Flooring
- White Vinyl Interior Sidewall Liner
- ATP Kickplate (12"H)
- 12v LED Interior Dome Lights (2) with Switch
- 12v LED Exterior Lighting Tail/Clearance Lights
- LED Rear ID Bar with Loading Light
- 1-Piece Aluminum Roof
- Bonded (*Screwless*) .030 Aluminum Exterior
- Non-Powered Roof Vent
- Flow-Thru Sidewall Vents
- 5,000 lb. D-Rings
- 24" ATP Stoneguard
- 14" x 14" Access Door
- Aluminum Fold-Down Step
- 6 Year Limited Warranty



Trailers shown may feature optional equipment available at additional cost.



www.wellscargo.com

Specifications, features, options, packages & pricing subject to change without notice. See your authorized Wells Cargo® dealer for more information.